

Chetco Digital Instruments

Chetco Digital Instruments, Inc.

SeaSwitch Remote Pro - Stand Alone 12 Channel

\$845.00



Â

The wireless Bluetooth and Wi-Fi option support NMEA 0183 with optional NMEA 2000 formatting. Switch status can be transmitted, controlled and displayed on NMEA 0183 or NMEA 2000 devices in multiple locations simultaneously. The network interface options allows all switches to be remotely controlled via SeaGauge color touch screens, PC based applications, or other devices.

Included with SeaSwitch is the vDash Instrumentation design software which allows customized switch labels to be set up on PC/Laptop and downloaded to the unit. Control of all switch states is possible from any PC computer or from any SeaGauge color touch display. Switch positions are chosen by the user and can be labeled in any language or choose international standard icons from our extensive library.

The SeaSwitch Remote PRO Switch Unit provides reliable switching operation via any of the SeaGauge color touch panels or an attached PC/Laptop. Each sealed switch unit contains 12 independent relays (SPST 15 AMPS) that can be operated remotely from an attached SeaGauge color touch screen display or directly over USB/Serial link. The heavy duty relays allow touch screen activation of a variety of equipment including NAV Lights, Bilge Pumps, Blowers, Running Light, Spots Lights, Cabin Lights, and much more. With the addition of a network interface module - direct control of switches is possible from any WEB browser or internet connection worldwide.

SeaSwitch Remote is housed in a solid ABS water-tight box measuring 8.2" wide x 2.28" tall x 2.5" deep.

SeaSwitch Remote Features:

- 12 function digital switch (with optional NMEA 2000 interface)
- Switches and Gauges can be displayed and controlled from one display or multiple displays using touch activated screens
- Switches can be interfaced with gauges and set to trigger when gauge min/max alarm thresholds are breached
- NMEA 2000 and NMEA 0183 command status via serial ports
- 15 Amp relay on each circuit
- Remote control and status viewing on Windows PC, PDA or SeaGauge color display
- Sealed water resistant design
- User defined switch labels (multiple languages) and display positions
- Ethernet, Bluetooth and Wi-Fi wireless data transmission option available

[Vendor Information](#)

There are yet no reviews for this product.

Please log in to write a review.